

01 Specs 01Titel	SPA 22-23	20.03.17 KF VS.01	Project No.																																																		
Item / No.	Description/ Quantity/ Unit	Unit price	Total price																																																		
01.1 Position	<p>Description: Submersible pump, suitable for clean water. Can be installed vertically or horizontally. The pump is fitted with sand shield, lip seal, water-lubricated journal bearings and a volume compensating diaphragm. The motor is a canned type submersible motor offering good mechanical stability and high efficiency.</p> <p>Suitable for wet assembly.</p> <p>Environmental conditions for wet application (waterquality): Installation and operation in fresh-, pool- and seawater.*</p> <p>Technical data:</p> <table> <tbody> <tr> <td>Weight:</td> <td>20 Kg</td> </tr> <tr> <td>Dimensions (Lx W x H): incl. Filter</td> <td>680x225x237 [mm]</td> </tr> <tr> <td>Speed for pump data:</td> <td>2900 1/min</td> </tr> <tr> <td>Rated flow:</td> <td>17 m³/h</td> </tr> <tr> <td>Rated head:</td> <td>15 m</td> </tr> <tr> <td>Approvals on nameplate:</td> <td>CE,EAC</td> </tr> <tr> <td>Curve tolerance:</td> <td>ISO9906:2012 3B</td> </tr> <tr> <td>Motor version:</td> <td>T40</td> </tr> </tbody> </table> <p>Materials:</p> <table> <tbody> <tr> <td>Pump:</td> <td>Stainless steel /EN 1.4301/ AISI 304</td> </tr> <tr> <td>Impeller:</td> <td>Stainless steel /EN 1.4301/ AISI 304</td> </tr> <tr> <td>Motor:</td> <td>Stainless steel /EN 1.4301/ AISI 304</td> </tr> <tr> <td>Shaft seal for motor:</td> <td>Lipseal</td> </tr> </tbody> </table> <p>Installation:</p> <table> <tbody> <tr> <td>Pump outlet (Inside thread):</td> <td>RP2 1/2</td> </tr> </tbody> </table> <p>Electrical data:</p> <table> <tbody> <tr> <td>Motor type:</td> <td>MS402</td> </tr> <tr> <td>Rated power - P2:</td> <td>1.1 kW</td> </tr> <tr> <td>Power (P2) required by pump:</td> <td>1.1 kW</td> </tr> <tr> <td>Mains frequency:</td> <td>50 Hz</td> </tr> <tr> <td>Rated voltage:</td> <td>3 x 400 V</td> </tr> <tr> <td>Rated current:</td> <td>3.4 A</td> </tr> <tr> <td>Starting current:</td> <td>4,8</td> </tr> <tr> <td>Cos phi- power factor:</td> <td>0.72</td> </tr> <tr> <td>Rated speed:</td> <td>2860 1/min</td> </tr> <tr> <td>Start method:</td> <td>Direct online</td> </tr> <tr> <td>Enclosure class (IEC 34-5):</td> <td>IP68</td> </tr> <tr> <td>Insulation class(IEC 85):</td> <td>B</td> </tr> </tbody> </table>	Weight:	20 Kg	Dimensions (Lx W x H): incl. Filter	680x225x237 [mm]	Speed for pump data:	2900 1/min	Rated flow:	17 m ³ /h	Rated head:	15 m	Approvals on nameplate:	CE,EAC	Curve tolerance:	ISO9906:2012 3B	Motor version:	T40	Pump:	Stainless steel /EN 1.4301/ AISI 304	Impeller:	Stainless steel /EN 1.4301/ AISI 304	Motor:	Stainless steel /EN 1.4301/ AISI 304	Shaft seal for motor:	Lipseal	Pump outlet (Inside thread):	RP2 1/2	Motor type:	MS402	Rated power - P2:	1.1 kW	Power (P2) required by pump:	1.1 kW	Mains frequency:	50 Hz	Rated voltage:	3 x 400 V	Rated current:	3.4 A	Starting current:	4,8	Cos phi- power factor:	0.72	Rated speed:	2860 1/min	Start method:	Direct online	Enclosure class (IEC 34-5):	IP68	Insulation class(IEC 85):	B		
Weight:	20 Kg																																																				
Dimensions (Lx W x H): incl. Filter	680x225x237 [mm]																																																				
Speed for pump data:	2900 1/min																																																				
Rated flow:	17 m ³ /h																																																				
Rated head:	15 m																																																				
Approvals on nameplate:	CE,EAC																																																				
Curve tolerance:	ISO9906:2012 3B																																																				
Motor version:	T40																																																				
Pump:	Stainless steel /EN 1.4301/ AISI 304																																																				
Impeller:	Stainless steel /EN 1.4301/ AISI 304																																																				
Motor:	Stainless steel /EN 1.4301/ AISI 304																																																				
Shaft seal for motor:	Lipseal																																																				
Pump outlet (Inside thread):	RP2 1/2																																																				
Motor type:	MS402																																																				
Rated power - P2:	1.1 kW																																																				
Power (P2) required by pump:	1.1 kW																																																				
Mains frequency:	50 Hz																																																				
Rated voltage:	3 x 400 V																																																				
Rated current:	3.4 A																																																				
Starting current:	4,8																																																				
Cos phi- power factor:	0.72																																																				
Rated speed:	2860 1/min																																																				
Start method:	Direct online																																																				
Enclosure class (IEC 34-5):	IP68																																																				
Insulation class(IEC 85):	B																																																				

01 Specs 01Titel	SPA 22-23			20.03.17 KF VS.01	Project No.																																																
Item / No.	Description/ Quantity/ Unit			Unit price	Total price																																																
* water-quality-matrix																																																					
<table border="1"> <thead> <tr> <th></th> <th>Freshwater</th> <th>Poolwater</th> <th>Seawater</th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>PH.Value</td> <td>7,2 -7,6</td> <td>7,2 -7,6</td> <td>8</td> <td></td> <td></td> </tr> <tr> <td>Hardness</td> <td>8 -15 ° DH; 142 -267 ppm CaCo3</td> <td>8 -15 ° DH; 142 -267 ppm CaCo3</td> <td>20 -30 ° DH; 356 - 534 ppm CaCo3</td> <td></td> <td></td> </tr> <tr> <td>Free Chlorine</td> <td>< 0,3 mg/l; < 0,036 moz/gal</td> <td>0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td> <td>< 0,3 mg/l; < 0,036 moz/gal</td> <td></td> <td></td> </tr> <tr> <td>Chlorine concentration</td> <td>< 250 mg/l; < 30,28 moz/gal</td> <td>< 200 mg/l; < 24,2 moz/gal</td> <td><=22000 mg/l; <=2664 moz/gal</td> <td></td> <td></td> </tr> <tr> <td>Salinity</td> <td>n. d.</td> <td>n. d.</td> <td><= 4%; <= 40.000 ppm</td> <td></td> <td></td> </tr> <tr> <td>Total Dry Residue</td> <td>< 50 mg/l; < 6,06 moz/gal</td> <td>< 50 mg/l; < 6,06 moz/gal</td> <td>< 250mg/l; < 30,28 moz/gal</td> <td></td> <td></td> </tr> <tr> <td>Temperature</td> <td>4 -35° C; 39 - 95 ° F</td> <td>4 -30° C; 39 - 86 ° F</td> <td>4 - 20 ° C; 39 - 68 ° F</td> <td></td> <td></td> </tr> </tbody> </table>							Freshwater	Poolwater	Seawater			PH.Value	7,2 -7,6	7,2 -7,6	8			Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3			Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal			Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal			Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm			Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal			Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
	Freshwater	Poolwater	Seawater																																																		
PH.Value	7,2 -7,6	7,2 -7,6	8																																																		
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																																		
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																																		
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																																		
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																																		
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																																		
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																																		
Supply and delivery according to manufacturer specifications.																																																					
Product / proof of delivery: SPA 22-23 Art. 53834																																																					
OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800																																																					
(or equivalent) Entered by the bidder																																																					